# **FLAT BALE OPENER BO2000**

FLAT BALE OPENER FOR INNER SPRING UNITS





#### introduction

## flat bale opener

#### model BO2000

A safe, convenient and easy way to unpack flat pressed inner-spring units, bundled in a bale. Maximum bale size 200 x 200 cm (80"x80").

Safety guards round the platforms prevents over spilling and possible accidents when opening.

Maximum opening, distance between top and bottom platform, 245 cm (97")

Useful opening 218 cm (86").

Can open more than 8 bales an hour.

The motorized screw type action provides extra safety and durability.

Can open any type of spring units with or without frame.

Emergency sensors round the top moving platform stops the machine in case of blockage.



## operation



The bale is positioned on the lower platform. The top platform with a built-in sensor ensures that it will automatically come to a halt just above the bale when lowered.

Through the top platform, the straps are cut and then the platform is raised to release the spring units to be collected.


Power requirement: 3 kW three phase

Shipping Weight: 1250 kg

Dimensions: 230 x 212 x 300 cm height



Working space required



aneco INDUSTRIES LTD

Offices and Factory

39, Kalamon Street 2032 Strovolos Industrial Zone Nicosia - CYPRUS

Tel. +357 22 484444 Fax +357 22 481360 Postal Address

P.O.Box 22361 1520 Nicosia CYPRUS

E-Mail : info@amelco.com http://www.amelco.com