

# FLAT BALING MACHINE FB22

EASY, SAFE AND FLEXIBLE METHOD TO FLATPACK SPRING UNITS



## introduction

A practical, easy and fast way to press Spring Units in FLAT bales.

## flat baler

Ideal for Spring Units with Round Border Wire.  
Easy and safe stacking, storing and transport.  
No distortion of Spring Units.  
At least 10 times space saving.  
Heavy-duty construction, overall pressure up to 5000 kilos.  
Safe and easy operation.  
Controls on either side of the machine.  
Variable speed controlled by inverter, with independent choice both on compression and on return cycle.  
Centering device to accommodate any width of spring units.  
Pre-selected thickness of bale to avoid human error and damaging the Spring Units

## model FB22



## operation

The spring units are placed vertically between the two compression platforms and flat wooden pallets.  
After the insertion of stabilizing poles through the units, the springs are compressed to the desired size (thickness).  
The poles are removed and the bale is removed after strapping.



## specifications

### Standard size machine (FB22)

**Maximum Size of Spring Units :** 200cm x 200cm.  
**Maximum Opening :** 250cm (18 units 13cm height).  
**Minimum Bale thickness :** 15cm.  
**Compression speed :** 1.5 meters/min (adjustable).  
**Return speed :** 2.0 meters/min (adjustable).  
Expected production about 5 bales/hour with two operators.  
Minimal Installation requirements needed.

**Overall Shipping Dimensions (cm) :** 300x225x240(height)  
**Shipping Weight :** 1825 kilos  
**Electrical Power Supply :** 3kW, 3phase

### Other machine sizes available on order



Offices and Factory

39, Kalamon Street  
2032 Strovolos Industrial Zone  
Nicosia - CYPRUS

Tel. +357 22 484444  
Fax +357 22 481360

Postal Address

P.O.Box 22361  
1520 Nicosia  
CYPRUS

E-Mail : [info@amelco.com](mailto:info@amelco.com)  
<http://www.amelco.com>

